



REV	CHG.	DATE	DESCRIPTION	REVISION

Pin No.	Signal
A	U
B	V
C	W
D	FG
1	—
2	—

Pin No.	Signal
1	SD+
2	SD-
3	BAT+
4	BAT-
7	Gnd
8	Vcc
10	FG

מק"ט	משקל	LL	LR	QK	S	KB1	W	WK	M	D
UMM-0029EA-B6	14.6kg	160	79	65	35	135.5	10	38	12	25
UMM-0044EA-B6	17.6kg	179	79	65	35	154.5	10	38	12	25
UMM-0055EA-B6	23.2kg	211	113	96	42	186.5	12	45	16	32
UMM-0075EA-B6	29kg	247	113	96	42	222.5	12	45	16	32

SOURCE DRAWING-FOR REFERENCE ONLY

APPROVED BY		DATE	
CHECKED BY		DATE	
DRAWING BY	Doron	DATE	07.05.2024
TOLERANCE UNLESS OTHERWISE SPECIFIED	CABLE LENGTH	TOLERANCE	
	ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0%(OR 0mm) OF LENGTH WHICHEVER IS GREATER	
	STRIP LENGTH	TOLERANCE	
	0-7mm	±1.0mm	
	8-29mm	±1.5mm	
	30-49mm	±2.0mm	
50-99mm	±3.0mm		
100-199mm	±4.0mm		
over 200mm	±5.0mm		

UNITRONICS®

UNITS	mm	DESCRIPTION: 400VAC, 2.9kW~7.5kW, B6
1st Angle Projection		
		PART NO.
REV	A	SHEET
		1 OF 1