

REV	CHG.	DATE	DESCRIPTION	REVISION


Pin No.	Signal
A	U
B	V
C	W
D	FG
1	B1
2	B2

Pin No.	Signal
1	SD+
2	SD-
3	BAT+
4	BAT-
7	Gnd
8	Vcc
10	FG


מק"ט	משקל	LL	LR	QK	S	KB1	W	WK	M	D
UWM-0029EAB-B6	18.8kg	205	79	65	35	139.8	10	38	12	25
UWM-0044EAB-B6	21.8kg	224	79	65	35	158.8	10	38	12	25
UWM-0055EAB-B6	27.8kg	264	113	96	42	198.8	12	45	16	32
UWM-0075EAB-B6	33.6kg	300	113	96	42	234.8	12	45	16	32

SOURCE DRAWING-FOR REFERENCE ONLY

APPROVED BY		DATE	
CHECKED BY		DATE	
DRAWING BY	Doron	DATE	07.05.2024
TOLERANCE UNLESS OTHERWISE SPECIFIED	CABLE LENGTH	TOLERANCE	
	ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0%(OR 0mm) OF LENGTH WHICHEVER IS GREATER	
	STRIP LENGTH	TOLERANCE	
	0-7mm	±1.0mm	
	8-29mm	±1.5mm	
	30-49mm	±2.0mm	
50-99mm	±3.0mm		
70-100mm	±4.0mm		
over 100mm	±5.0mm		



UNITRONICS®

UNITS	mm	DESCRIPTION:
1st Angle Projection		400VAC, 2.9kW~7.5kW, B6_BR
		PART NO.
REV	A	SHEET
		1 OF 1